

Backport21 - Backport #10265

Backport r45715 to fix configure on OpenBSD/NetBSD

09/19/2014 04:38 PM - jeremyevans0 (Jeremy Evans)

Status:	Closed
Priority:	Normal
Assignee:	nagachika (Tomoyuki Chikanaga)
Description	
In ruby 2.1.3, line 2095 of configure.in is: AC_MSG_RESULT(\${setjmp_prefix}setjmp\${setjmp_suffix}\${setjmp_cast:+(\$setjmp_cast)}) This substitution: \${setjmp_cast:+(\$setjmp_cast)} is not valid sh syntax for OpenBSD/NetBSD at least, though it is valid bash syntax. This was fixed in trunk in r45715 to use: \${setjmp_cast:+(\$setjmp_cast)} which works in OpenBSD/NetBSD. I request that r45715 be backported to the ruby_2_1 branch before the 2.1.4 release.	

Associated revisions

Revision da85f4ee - 10/15/2014 02:47 PM - nagachika (Tomoyuki Chikanaga)

merge revision(s) r45715: [Backport #10265]

```
* configure.in: NetBSD's ksh, used by configure, needs escapes.
```

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/branches/ruby_2_1@47952 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 47952 - 10/15/2014 02:47 PM - nagachika (Tomoyuki Chikanaga)

merge revision(s) r45715: [Backport #10265]

```
* configure.in: NetBSD's ksh, used by configure, needs escapes.
```

History

#1 - 10/15/2014 02:16 PM - nagachika (Tomoyuki Chikanaga)

- Status changed from Open to Assigned
- Assignee set to nagachika (Tomoyuki Chikanaga)

#2 - 10/15/2014 02:47 PM - nagachika (Tomoyuki Chikanaga)

- Status changed from Assigned to Closed
- % Done changed from 0 to 100

Applied in changeset [r47952](#).

merge revision(s) r45715: [Backport [#10265](#)]

```
* configure.in: NetBSD's ksh, used by configure, needs escapes.
```