

Ruby master - Bug #11677

52530 sprintf hash key value nil KeyError

11/11/2015 08:14 AM - yui-knk (Kaneko Yuichiro)

Status: Closed	
Priority: Normal	
Assignee:	
Target version:	
ruby -v: ruby 2.3.0dev (trunk 52534) [x86_64-darwin14]	Backport: 2.0.0: DONTNEED, 2.1: DONTNEED, 2.2: DONTNEED
Description <pre>def test_named_with_nil h = { key: nil, key2: "key2_val" } assert_equal("key is , key2 is key2_val", "key is %{key}, key2 is %{key2}" % h) end</pre> <p>2.2.3 trunk</p> <pre>KeyError: key{key} not found</pre> <p></p> <pre>"a.hoge is %{a}, b.fuga is %{b}" % { a: a.hoge, b: b.fuga }</pre> <pre>value nil key</pre>	
Related issues: Related to Ruby master - Bug #11661: sprintf causes a KeyError instead of usi... Closed	

Associated revisions

Revision 56e3b493 - 11/11/2015 09:30 AM - nobu (Nobuyoshi Nakada)

sprintf.c: nil value is valid

- sprintf.c (rb_str_format): look up the key, then get default value and raise KeyError if the returned value is nil. [ruby-dev:49338] [Ruby trunk - Bug #11677]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@52537 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 52537 - 11/11/2015 09:30 AM - nobu (Nobuyoshi Nakada)

sprintf.c: nil value is valid

- sprintf.c (rb_str_format): look up the key, then get default value and raise KeyError if the returned value is nil. [ruby-dev:49338] [Ruby trunk - Bug #11677]

Revision 52537 - 11/11/2015 09:30 AM - nobu (Nobuyoshi Nakada)

sprintf.c: nil value is valid

- sprintf.c (rb_str_format): look up the key, then get default value and raise KeyError if the returned value is nil. [ruby-dev:49338] [Ruby trunk - Bug #11677]

Revision 52537 - 11/11/2015 09:30 AM - nobu (Nobuyoshi Nakada)

sprintf.c: nil value is valid

- sprintf.c (rb_str_format): look up the key, then get default value and raise KeyError if the returned value is nil. [ruby-dev:49338] [Ruby trunk - Bug #11677]

Revision 52537 - 11/11/2015 09:30 AM - nobu (Nobuyoshi Nakada)

sprintf.c: nil value is valid

- sprintf.c (rb_str_format): look up the key, then get default value and raise KeyError if the returned value is nil. [ruby-dev:49338] [Ruby trunk - Bug #11677]

#11677]

Revision 52537 - 11/11/2015 09:30 AM - nobu (Nobuyoshi Nakada)

sprintf.c: nil value is valid

- sprintf.c (rb_str_format): look up the key, then get default value and raise KeyError if the returned value is nil. [ruby-dev:49338] [Ruby trunk - Bug #11677]

History

#1 - 11/11/2015 09:27 AM - yui-knk (Kaneko Yuichiro)

- File deleted (0001-Not-raise-KeyError-when-an-arg-hash-of-sprintf-has-k.patch)

#2 - 11/11/2015 09:28 AM - yui-knk (Kaneko Yuichiro)

- File 0001-Not-raise-KeyError-when-an-arg-hash-of-sprintf-has-k.patch added

#3 - 11/11/2015 09:30 AM - nobu (Nobuyoshi Nakada)

- Status changed from Open to Closed

Applied in changeset r52537.

sprintf.c: nil value is valid

- sprintf.c (rb_str_format): look up the key, then get default value and raise KeyError if the returned value is nil. [ruby-dev:49338] [Ruby trunk - Bug [#11677](#)]

#4 - 11/11/2015 09:45 AM - yui-knk (Kaneko Yuichiro)

□□□□□□□□□□

#5 - 11/11/2015 01:34 PM - naruse (Yui NARUSE)

- Backport changed from 2.0.0: UNKNOWN, 2.1: UNKNOWN, 2.2: UNKNOWN to 2.0.0: DONTNEED, 2.1: DONTNEED, 2.2: DONTNEED

#6 - 11/18/2015 11:28 AM - usa (Usaku NAKAMURA)

- Related to Bug #11661: sprintf causes a KeyError instead of using a default value for hash substitution added

Files

0001-Not-raise-KeyError-when-an-arg-hash-of-sprintf-has-k.patch	1.44 KB	11/11/2015	yui-knk (Kaneko Yuichiro)
---	---------	------------	---------------------------