

Ruby trunk - Feature #15373

Proposal: Enable refinements to `#method` and `#instance_method`

12/03/2018 08:47 AM - osyo (manga osyo)

Status:	Closed
Priority:	Normal
Assignee:	
Target version:	
Description	
<p>Proposal enable refinements to <code>#method</code> and <code>#instance_method</code>. It can be used in the following cases.</p> <pre># default call to #pp module P2PP refine Kernel do def p obj pp obj end end end using P2PP # call to Kernel.#pp [1, 2, 3].map(&method(:p))</pre> <p>Also, when checking the defined position as follows, the refine place is reflected.</p> <pre>module P2PP refine Kernel do def p obj pp obj end end end # Output to refine defined position # Before p method(:p).source_location # => nil p Kernel.instance_method(:p).source_location # => nil using P2PP # After p method(:p).source_location # => ["../ruby/test.rb", 4] p Kernel.instance_method(:p).source_location # => ["../ruby/test.rb", 4]</pre> <p>I want <code>..</code> operators to work. https://bugs.ruby-lang.org/issues/13581</p> <p>pull request: https://github.com/ruby/ruby/pull/2034</p>	

Associated revisions

Revision 66935 - 01/28/2019 11:45 AM - nobu (Nobuyoshi Nakada)

Add refinements support to `method/instance_method`.

[Fix GH-2034]

From: manga_osyo manga.osyo@gmail.com

History

#1 - 12/03/2018 09:20 AM - shevegen (Robert A. Heiler)

I won't comment on the `.`: here and not about the first part of the suggestions here either, but about `.source_location` I agree as that would make sense (to me at the least).

Returning something that exists is better than returning `nil` in this context. In a REPL this can be useful too since one can e. g. automatically "jump" to the code in question and modify it (I think pry is doing something like this).

I think matz has to decide whether he wants that functionality to work (in regards to `.source_location`; I don't refer to the other parts of the issue).

If approved I would then recommend, if it is changed, to also add a comment for the documentation of `.source_location` to mention that it works with refinements too, and perhaps add an example, similar to the one in this issue request:

https://ruby-doc.org/core/Method.html#method-i-source_location

#2 - 12/03/2018 11:16 AM - osyo (manga osyo)

Thank you! shevegen :)

#3 - 01/28/2019 01:52 PM - nobu (Nobuyoshi Nakada)

- *Status changed from Open to Closed*