

# Ruby master - Feature #2372

## read\_all() with buffering

11/15/2009 09:21 PM - wanabe (\_ wanabe)

<b>Status:</b>	Closed
<b>Priority:</b>	Normal
<b>Assignee:</b>	
<b>Target version:</b>	2.0.0

**Description**

```
=begin
io.c read_all()
io_shift_cbuf()
io_shift_cbuf()

bm_io_file_read.rb
Windows 'r' 'rb'

2.8
Windows

=end
```

### History

#1 - 11/15/2009 09:50 PM - mame (Yusuke Endoh)

```
=begin

```

2009111521:21 \_ wanabe [redmine@ruby-lang.org](mailto:redmine@ruby-lang.org):

```
io.c read_all()
io_shift_cbuf()
io_shift_cbuf()
```

```
2.8
```

```
Windows
```

Debian 2.8

```
$. /ruby test.rb
user system total real
short r 0.310000 0.190000 0.500000 ( 0.489743)
short r:us-ascii:utf-8 0.760000 0.220000 0.980000 ( 0.984798)
short r:us-ascii:utf-16le 1.030000 0.270000 1.300000 ( 1.293715)
short rb 0.260000 0.220000 0.480000 ( 0.480045)
short rb:us-ascii:utf-8 0.730000 0.260000 0.990000 ( 1.005522)
short rb:us-ascii:utf-16le 1.050000 0.250000 1.300000 ( 1.311958)
long r 0.040000 0.020000 0.060000 ( 0.057341)
long r:us-ascii:utf-8 3.800000 0.020000 3.820000 ( 3.817237)
long r:us-ascii:utf-16le 7.840000 0.040000 7.880000 ( 7.956883)
long rb 0.020000 0.030000 0.050000 ( 0.052485)
long rb:us-ascii:utf-8 3.830000 0.030000 3.860000 ( 3.867369)
long rb:us-ascii:utf-16le 7.960000 0.020000 7.980000 ( 8.031679)
```

```
$. /ruby.org test.rb
user system total real
short r 0.280000 0.190000 0.470000 ( 0.459421)
```





```

short r      3.093000  6.422000  9.515000 ( 9.734375)
short r:us-ascii:utf-8  4.469000  7.031000  11.500000 ( 12.171875)
short r:us-ascii:utf-16le 5.688000  7.156000  12.844000 ( 13.375000)
short rb     1.906000  5.875000  7.781000 ( 8.031250)
short rb:us-ascii:utf-8  3.906000  6.344000  10.250000 ( 10.609375)
short rb:us-ascii:utf-16le 4.297000  7.047000  11.344000 ( 11.937500)
long r       1.969000  0.219000  2.188000 ( 2.218750)
long r:us-ascii:utf-8   13.407000  0.281000  13.688000 ( 14.093750)
long r:us-ascii:utf-16le 20.515000  0.344000  20.859000 ( 21.515625)
long rb      0.078000  0.203000  0.281000 ( 0.328125)
long rb:us-ascii:utf-8  1.625000  0.297000  1.922000 ( 2.031250)
long rb:us-ascii:utf-16le 12.891000  0.531000  13.422000 ( 13.968750)

```

```
--

```

```
=end
```

#7 - 11/18/2009 10:52 PM - matz (Yukihiro Matsumoto)

```
=begin

```

In message "Re: [ruby-dev:39708] Re: [Feature #2372](#) read\_all() with buffering" on Wed, 18 Nov 2009 07:16:32 +0900, Tanaka Akira [akr@fsij.org](mailto:akr@fsij.org) writes:

```

|ECONV_AFTER_OUTPUT
|
|
|

```

```


```

```
=end
```

**Files**

buffering_readall.patch	1.1 KB	11/15/2009	wanabe (_ wanabe)
test.rb	565 Bytes	11/15/2009	wanabe (_ wanabe)
log.txt	2.06 KB	11/15/2009	wanabe (_ wanabe)