

Ruby trunk - Bug #3925

setting Tempfile/StringIO to \$std* before startup causes [BUG] Segmentation fault

10/11/2010 04:03 AM - arton (Akio Tajima)

Status: Closed	
Priority: Normal	
Assignee:	
Target version: 2.0.0	
ruby -v: ruby 1.9.2p0 (2010-08-18 revision 29036) [i386-mswin32_100]	Backport: 2.3: UNKNOWN, 2.4: UNKNOWN
Description	
<pre>=begin \$stdout, in, err, Tempfile, StringIO, r, [BUG] #d.rb require 'stringio' \$stdout = StringIO.new #----- \$ruby -r./d -e 'puts "hello"' -e: [BUG] Segmentation fault ruby 1.9.2p0 (2010-08-18 revision 29036) [i386-mswin32_100] -- control frame ----- c:0001 p:0000 s:0002 b:0002 l:00122c d:00122c TOP Tempfile, StringIO, set_encoding --- io.c.org Sat Jul 24 19:38:33 2010 +++ io.c Mon Oct 11 03:47:30 2010 @@ -8652,9 +8652,9 @@ rb_stdio_set_default_encoding(void) extern VALUE rb_stdin, rb_stdout, rb_stderr; VALUE val = Qnil; • rb_io_set_encoding(1, &val, rb_stdin); • rb_io_set_encoding(1, &val, rb_stdout); • rb_io_set_encoding(1, &val, rb_stderr); • rb_funcall3(rb_stdin, rb_intern("set_encoding"), 1, &val); • rb_funcall3(rb_stdout, rb_intern("set_encoding"), 1, &val); • rb_funcall3(rb_stderr, rb_intern("set_encoding"), 1, &val); } /* -r =end</pre>	

History

#1 - 10/11/2010 06:37 AM - naruse (Yui NARUSE)

- Status changed from Open to Closed

- % Done changed from 0 to 100

=begin

This issue was solved with changeset [r29435](#).

Akio, thank you for reporting this issue.

Your contribution to Ruby is greatly appreciated.

May Ruby be with you.

=end