

Ruby trunk - Feature #4568

[PATCH] file.c (rb_group_member): kill 256K of stack usage

04/11/2011 04:01 PM - normalperson (Eric Wong)

Status:	Closed
Priority:	Normal
Assignee:	kosaki (Motohiro KOSAKI)
Target version:	2.0.0
Description	
=begin It was using 256K stack on my x86_64 machine. Found with scripts/checkstack.pl in the Linux kernel source: objdump -D ./ruby ~/linux-2.6/scripts/checkstack.pl x86_64 Also pushed to my repo: git pull git://bogomips.org/ruby stack-reduce =end	

History

#1 - 04/11/2011 05:23 PM - normalperson (Eric Wong)

=begin
Lowering RUBY_STACK_MIN_LIMIT to 64KB across the board in
thread_pthread.c seems to work fine for check, test-rubyspec,
benchmark-each.

No real code, though, and I also don't know what outside C extensions
do, but 64KB is the PTHREAD_STACK_MIN for my platform (and I've always
felt it was too high).

```
diff --git a/thread_pthread.c b/thread_pthread.c
index ad6f716..a015873 100644
--- a/thread_pthread.c
+++ b/thread_pthread.c
@@ -630,11 +630,7 @@ use_cached_thread(rb_thread_t *th)
 }

enum {
-#ifdef SYMBIAN32
-  RUBY_STACK_MIN_LIMIT = 64 * 1024, /* 64KB: Let's be slightly more frugal on mobile platform /
-#else
-  RUBY_STACK_MIN_LIMIT = 512 * 1024, /512KB /
-#endif
+  RUBY_STACK_MIN_LIMIT = 64 * 1024, /64KB */
  RUBY_STACK_SPACE_LIMIT = 1024 * 1024
};
```

--
Eric Wong
=end

#2 - 04/11/2011 09:19 PM - kosaki (Motohiro KOSAKI)

- Status changed from Open to Closed
- Assignee set to kosaki (Motohiro KOSAKI)

```
=begin  
Committed by r31259.  
=end
```

#3 - 04/12/2011 08:18 PM - normalperson (Eric Wong)

```
=begin  
Lowering RUBY_STACK_MIN_LIMIT to 64KB across the board in  
thread_pthread.c seems to work fine for check, test-rubyspec,  
benchmark-each.
```

No real code, though, and I also don't know what outside C extensions do, but 64KB is the PTHREAD_STACK_MIN for my platform (and I've always felt it was too high).

```
diff --git a/thread_pthread.c b/thread_pthread.c  
index ad6f716..a015873 100644  
--- a/thread_pthread.c  
+++ b/thread_pthread.c  
@@ -630,11 +630,7 @@ use_cached_thread(rb_thread_t *th  
}  
  
enum {  
-#ifdef SYMBIAN32  
- RUBY_STACK_MIN_LIMIT = 64 * 1024, /* 64KB: Let's be slightly more frugal on mobile platform /  
-#else  
- RUBY_STACK_MIN_LIMIT = 512 * 1024, /512KB /  
-#endif  
+ RUBY_STACK_MIN_LIMIT = 64 * 1024, /64KB */  
RUBY_STACK_SPACE_LIMIT = 1024 * 1024  
};  
  
--  
Eric Wong  
=end
```

#4 - 04/13/2011 08:45 AM - normalperson (Eric Wong)

=begin

Eric Wong normalperson@yhbt.net wrote:

Lowering RUBY_STACK_MIN_LIMIT to 64KB across the board in thread_pthread.c seems to work fine for check, test-rubyspec, benchmark-each.

No real code, though, and I also don't know what outside C extensions do, but 64KB is the PTHREAD_STACK_MIN for my platform (and I've always felt it was too high).

I was wrong about 64KB on my system 16KB is the minimum with NPTL :x

The lowest successful stack size I've been able to run is 48K, I get stack corruption and GC failures with 44K and lower.

I've also run my Rainbows! web server[1] integration/torture test suite with several threaded options and everything passed with 48K and didn't notice ill effects. 44K seemed fine, too, I think, but 32K failed Rainbows! tests miserably.

To be on the safe side with existing code/extensions and maybe some overaggressive alloca() calls, I think 64KB is reasonable.

[1] - <http://rainbows.rubyforge.org/> + <http://bogomips.org/rainbows.git>

--

Eric Wong

=end

Files

0001-file.c-rb_group_member-kill-256K-of-stack-usage.patch	1.21 KB	04/11/2011	normalperson (Eric Wong)
--	---------	------------	--------------------------