

Ruby trunk - Bug #4619

io.c is broken on Windows

04/27/2011 12:13 PM - usa (Usaku NAKAMURA)

Status: Closed	
Priority: Normal	
Assignee: nobu (Nobuyoshi Nakada)	
Target version: 1.9.3	
ruby -v: ruby 1.9.3dev (2011-04-27 trunk 31365) [x64-mswin64_100]	Backport:
Description =begin r31355 textmode (n)make test test-all E revert? make test: #339 test_literal.rb: echo foo #=> "foo\r\n" (expected "foo\n") #340 test_literal.rb: s = "foo"; echo #{s} #=> "foo\r\n" (expected "foo\n") make test-all E: Encoding::ConverterNotFoundError: code converter not found (universal_newline, crlf_newline) =end	
Related issues: Is duplicate of Ruby trunk - Bug #4618: Encoding::ConverterNotFoundError on ... Closed 04/27/2011	

Associated revisions

Revision 9c48e599 - 04/27/2011 09:06 PM - nobu (Nobuyoshi Nakada)

- io.c (rb_io_extract_modeenc, rb_f_backquote): set default text mode. fixes #4619
- io.c (pipe_open): set universal newline decorator if needed.

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@31367 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 31367 - 04/27/2011 09:06 PM - nobu (Nobuyoshi Nakada)

- io.c (rb_io_extract_modeenc, rb_f_backquote): set default text mode. fixes #4619
- io.c (pipe_open): set universal newline decorator if needed.

Revision 31367 - 04/27/2011 09:06 PM - nobu (Nobuyoshi Nakada)

- io.c (rb_io_extract_modeenc, rb_f_backquote): set default text mode. fixes #4619
- io.c (pipe_open): set universal newline decorator if needed.

Revision 31367 - 04/27/2011 09:06 PM - nobu (Nobuyoshi Nakada)

- io.c (rb_io_extract_modeenc, rb_f_backquote): set default text mode. fixes #4619
- io.c (pipe_open): set universal newline decorator if needed.

Revision 31367 - 04/27/2011 09:06 PM - nobu (Nobuyoshi Nakada)

- io.c (rb_io_extract_modeenc, rb_f_backquote): set default text mode. fixes #4619
- io.c (pipe_open): set universal newline decorator if needed.

Revision 31367 - 04/27/2011 09:06 PM - nobu (Nobuyoshi Nakada)

- io.c (rb_io_extract_modeenc, rb_f_backquote): set default text mode. fixes #4619
- io.c (pipe_open): set universal newline decorator if needed.

Revision 31367 - 04/27/2011 09:06 PM - nobu (Nobuyoshi Nakada)

- io.c (rb_io_extract_modeenc, rb_f_backquote): set default text mode. fixes #4619
- io.c (pipe_open): set universal newline decorator if needed.

Revision 85c1d5d4 - 04/29/2011 01:24 AM - nobu (Nobuyoshi Nakada)

- io.c (make_writeconv): do not add textmode newline decorator if any newline decorator is set already. fixes #4618, fixes #4619

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@31377 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 31377 - 04/29/2011 01:24 AM - nobu (Nobuyoshi Nakada)

- io.c (make_writeconv): do not add textmode newline decorator if any newline decorator is set already. fixes #4618, fixes #4619

Revision 31377 - 04/29/2011 01:24 AM - nobu (Nobuyoshi Nakada)

- io.c (make_writeconv): do not add textmode newline decorator if any newline decorator is set already. fixes #4618, fixes #4619

Revision 31377 - 04/29/2011 01:24 AM - nobu (Nobuyoshi Nakada)

- io.c (make_writeconv): do not add textmode newline decorator if any newline decorator is set already. fixes #4618, fixes #4619

Revision 31377 - 04/29/2011 01:24 AM - nobu (Nobuyoshi Nakada)

- io.c (make_writeconv): do not add textmode newline decorator if any newline decorator is set already. fixes #4618, fixes #4619

Revision 31377 - 04/29/2011 01:24 AM - nobu (Nobuyoshi Nakada)

- io.c (make_writeconv): do not add textmode newline decorator if any newline decorator is set already. fixes #4618, fixes #4619

Revision 31377 - 04/29/2011 01:24 AM - nobu (Nobuyoshi Nakada)

- io.c (make_writeconv): do not add textmode newline decorator if any newline decorator is set already. fixes #4618, fixes #4619

History

#1 - 04/28/2011 06:07 AM - nobu (Nobuyoshi Nakada)

- Status changed from Assigned to Closed

- % Done changed from 0 to 100

=begin

This issue was solved with changeset [r31367](#).

Usaku, thank you for reporting this issue.

Your contribution to Ruby is greatly appreciated.

May Ruby be with you.

- io.c (rb_io_extract_modeenc, rb_f_backquote): set default text mode. fixes [#4619](#)
- io.c (pipe_open): set universal newline decorator if needed. =end

#2 - 04/28/2011 02:54 PM - usa (Usaku NAKAMURA)

- Status changed from Closed to Assigned

=begin

test-all

95

=end

#3 - 04/29/2011 10:24 AM - nobu (Nobuyoshi Nakada)

- Status changed from Assigned to Closed

=begin

This issue was solved with changeset [r31377](#).
Jon, thank you for reporting this issue.
Your contribution to Ruby is greatly appreciated.
May Ruby be with you.

- io.c (make_writeconv): do not add textmode newline decorator if any newline decorator is set already. fixes [#4618](#), fixes [#4619](#) =end