

Ruby trunk - Feature #8675

Add Readline.point=(pos)

07/24/2013 03:03 AM - naruse (Yui NARUSE)

Status:	Closed
Priority:	Normal
Assignee:	kouji (Kouji Takao)
Target version:	2.1.0
Description	
r42146 00000000 \A 00000000000000rl_point 00000000000000000000	
diff --git a/ext/readline/readline.c b/ext/readline/readline.c index 714b08c..03ab724 100644 --- a/ext/readline/readline.c +++ b/ext/readline/readline.c @@ -808,6 +808,12 @@ readline_s_get_point(VALUE self) { return INT2NUM(rl_point); } +static VALUE +readline_s_set_point(VALUE self, VALUE pos) +{ <ul style="list-style-type: none">• rl_point = NUM2INT(pos);• return pos; +} #else #define readline_s_get_point rb_f_notimplement #endif @@ -1761,6 +1767,8 @@ Init_readline() readline_s_get_line_buffer, 0); rb_define_singleton_method(mReadline, "point", readline_s_get_point, 0);• rb_define_singleton_method(mReadline, "point=",• readline_s_set_point, 1); rb_define_singleton_method(mReadline, "set_screen_size", readline_s_set_screen_size, 2); rb_define_singleton_method(mReadline, "get_screen_size",	

Associated revisions

Revision a78713ce - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline_s_set_point, Init_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

git-svn-id: svn+ssh://ci.ruby-lang.org/ruby/trunk@42405 b2dd03c8-39d4-4d8f-98ff-823fe69b080e

Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline_s_set_point, Init_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline_s_set_point, Init_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline_s_set_point, Init_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline_s_set_point, Init_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

- ext/readline/readline.c (readline_s_set_point, Init_readline): add Readline.point=(pos). Patched by naruse. [ruby-dev:47535] [Feature #8675]

Revision 42405 - 08/06/2013 12:52 PM - kouji (Kouji Takao)

