

Ruby master - Bug #8715

openssl mkmf.log filled with other data

08/01/2013 04:21 PM - mpapis (Michal Papis)

Status: Closed	
Priority: Normal	
Assignee:	
Target version:	
ruby -v: ruby 2.0.0p247 (2013-06-27 revision 41674) [x86_64-darwin12.3.0]	Backport: 1.9.3: UNKNOWN, 2.0.0: UNKNOWN
Description =begin After compilation + installation of ruby I check the log: (({cat /Users/mpapis/.rvm/src/ruby-2.0.0-p247/ext/openssl/mkmf.log})) Failed to configure openssl. It will not be installed. Failed to configure -test-/win32/dln. It will not be installed. Failed to configure -test-/win32/fd_setsize. It will not be installed. Failed to configure dl/win32. It will not be installed. Failed to configure fiddle/win32. It will not be installed. Then I run: (((cd /Users/mpapis/.rvm/src/ruby-2.0.0-p247/ext/openssl/ ; ruby extconf.rb))) checking for t_open() in -Insl... no checking for socket() in -lsocket... no checking for assert.h... yes checking for openssl/ssl.h... yes checking for openssl/conf_api.h... yes checking for SSL_library_init() in openssl/ssl.h with -Werror=deprecated-declarations... no extconf.rb:62:in <main>: Ignore OpenSSL broken by Apple. (RuntimeError) Please use another openssl. (e.g. using configure --with-openssl-dir=/path/to/openssl') And check the log again: (({cat /Users/mpapis/.rvm/src/ruby-2.0.0-p247/ext/openssl/mkmf.log})) === OpenSSL for Ruby configurator === === Checking for system dependent stuff... === have_library: checking for t_open() in -Insl... ----- no "/usr/bin/clang -o conftest -I/Users/mpapis/.rvm/rubies/ruby-2.0.0-p247/include/ruby-2.0.0/x86_64-darwin12.3.0 -I/Users/mpapis/.rvm/rubies/ruby-2.0.0-p247/include/ruby-2.0.0/ruby/backward -I/Users/mpapis/.rvm/rubies/ruby-2.0.0-p247/include/ruby-2.0.0 -I. -D_XOPEN_SOURCE -D_DARWIN_C_SOURCE -D_DARWIN_UNLIMITED_SELECT -D_REENTRANT -O3 -I/Users/mpapis/.sm/pkg/active/include -fPIC -pipe conftest.c -L. -L/Users/mpapis/.rvm/rubies/ruby-2.0.0-p247/lib -L. -Z -L/Users/mpapis/.sm/pkg/active/lib -L/usr/lib -fPIC -Bstatic -fstack-protector -arch x86_64 -lruby-static -lpthread -ldl -lobjc " ... Is this intended behavior or a bug? =end	
Related issues: Is duplicate of Backport200 - Backport #8209: mkmf.log contains misplaced mes... Closed 04/03/2013	

History

#1 - 08/01/2013 04:33 PM - mpapis (Michal Papis)

=begin
After applying <http://www.rubyist.net/~eban/goto/r42213> from <https://bugs.ruby-lang.org/issues/7948>

The error changes to: (({cat /Users/mpapis/.rvm/src/ruby-2.0.0-p247/ext/openssl/mkmf.log}))

Ignore OpenSSL broken by Apple.
Please use another openssl. (e.g. using `configure --with-openssl-dir=/path/to/openssl')
Failed to configure openssl. It will not be installed.

And again i need to run (({ruby extconf.rb})) to see more details in the log.
=end

#2 - 08/01/2013 05:23 PM - akr (Akira Tanaka)

2013/8/1 mpapis (Michal Papis) mpapis@gmail.com:

Bug [#8715](#): openssl mkmf.log filled with other data
<https://bugs.ruby-lang.org/issues/8715>

After compilation + installation of ruby I check the log: ((cat /Users/mpapis/.rvm/src/ruby-2.0.0-p247/ext/openssl/mkmf.log))
Failed to configure openssl. It will not be installed.
Failed to configure -test-/win32/dln. It will not be installed.
Failed to configure -test-/win32/fd_setsize. It will not be installed.
Failed to configure dl/win32. It will not be installed.
Failed to configure fiddle/win32. It will not be installed.

r40080 on trunk may fix mkmf.log. (not tested with Ruby 2.0.0)

--

Tanaka Akira

#3 - 08/02/2013 07:14 AM - mpapis (Michal Papis)

yes it did fixed the log problem - please backport it

#4 - 08/03/2013 11:11 PM - nagachika (Tomoyuki Chikanaga)

- *Status changed from Open to Closed*

Hello,

I'd backported r40080 and r40081 to ruby_2_0_0.